

**HCB 2082**

Fully Integrated/Seamless



**LIEBHERR**

Quality, Design and Innovation

The **HCB 2082** offers elegant French door styling, with self-closing double freezer drawers, available in 36" design for custom kitchens. Choose from the fully integrated HCB 2082 concealed behind custom cabinetry, or the professional aesthetics of stainless steel panels. Standard accessories for this series are available for adapting to 80" or 84" high installation requirements. Smart interior design features include a stainless steel back wall which prevents dripping and the build-up of ice, and fully extendable SoftTelescopic freezer drawers which provide reliable self-retraction and soft closing.

The **HCB 2082** includes BioFresh technology, which helps foods retain their healthy vitamins, aromas, and appetizing appearance for significantly longer than in conventional refrigerators. The automatic IceMaker with fixed water connection produces perfect half-moon crescent ice cubes, which can be taken from freezer-to-table thanks to the removable ice bin.

Liebherr's DuoCooling system, with individual variable speed compressors, provides superior performance and efficiency, as well as advanced food preservation. The dual refrigeration system creates optimal conditions in both the refrigerator and freezer compartments, which lengthens the shelf life of foods for a healthier lifestyle. Individual silent cooling systems ensure accurate temperature and humidity controls so that your fresh foods never dry out.



## Fully Integrated/Seamless

### HCB 2082 PremiumPlus



Energy consumption (kWh/y)

Estimated Yearly Energy Cost in US \$\*

Sound rating dB(A)\*\*

Refrigerator capacity cu.ft. (l)

BioFresh comp. cu.ft. (l)

Freezer capacity cu.ft. (l)

Number of shelves

Number of door racks

Number of freezer drawers

Number of BioFresh drawers

Electronic control

Refrigerator temperature range °F (°C)\*\*\*

Freezer temperature range °F (°C)

Defrost type

Interior light

Water filter

IceMaker

Ice cube output lbs. (kg)/24h

Ice cube stock lbs. (kg)

SoftSystem

Door hinges

Product dimensions (H/W/D) in. (cm)

Cut out dimensions (H/W/D) in. (cm)

Net weight lbs. (kg)

Voltage V/Hz

556

67

43

12.9 (365)

2.4 (69)

6.0 (170)

4

6

2 with LED lighting

2 with LED lighting

MagicEye with digital temp. display, touch electronic

+37°F to +45°F (+3°C to +7°C)

+7°F to -17°F (-14°C to -27°C)

automatic

LED light column and LED ceiling lighting

yes

fixed water connection

3.1 (1.4)

7.9 (3.6)

yes

left/right

79 13/16" / 35 7/8" / 24 1/16" (202.7/91/61)

80"-81 5/8" / 36 1/16" / 24 5/8" (203.2-207.2/91.5/62.5)

359.3 (163.0)

115/60

\* Estimated energy cost will depend on utility rates and use. Estimated energy cost based on a national average electricity cost of 12 cents per kWh.

\*\* Noise output – according to EN 60704-3.

\*\*\* BioFresh bins temperatures 32°F (0°C).



**German Engineering:** Our superior products offer premium quality, cutting edge design, and innovative features that best fit your lifestyle. The use of high quality materials, perfectly detailed finishes, and elite cooling components are combined with the latest production processes, resulting in an outstanding cooling product.



**Energy Star:** The entire line of North American Liebherr appliances meet or exceed ENERGY STAR® rating requirements, greatly reducing greenhouse emissions and energy costs.




**BioFresh:** BioFresh guarantees the perfect climate for super-long-term freshness. Each drawer can be used individually and provides ideal humidity – HydroSafes with high humidity or DrySafes with low humidity – for a versatile storage solution of meats and cheeses as well as fruits and vegetables.



**DuoCooling:** The dual refrigeration system creates optimal conditions in both the refrigerator and freezer which lengthens the shelf life of food items for a healthier lifestyle. This technology also preserves the flavor and texture of foods since there is no transfer of unwanted air, moisture or food aroma between the two compartments.



**SuperCool/SuperFrost:** Simply quick chill and/or freeze fresh groceries to preserve optimum freshness and seal in flavors, textures as well as maintain essential vitamins and minerals.



**SuperQuiet:** Noise levels are kept to a minimum thanks to virtually silent, speed-controlled, and sound absorbing compressors. Alongside a low noise cooling circuit, these features ensure exact performance, energy efficiency, and SuperQuiet operation.



**SoftSystem:** Doors close automatically and gently from a minimum opening angle of approx. 30° thanks to our SoftSystem technology, which eliminates slamming even when shelves are fully loaded.




**Electronic Display:** Our intuitive electronic touch control panel ensures all functions are easy and convenient to use as well as guarantees that the settings selected remain accurate and constant.




**GlassLine:** The elegant yet tough GlassLine shelves are scratch resistant and easy to clean as well as dishwasher safe. The space-saving shelves are designed for organization and are completely adjustable to suit your needs and the contents of the refrigerator. Additionally, the lighting shines through for a brighter interior.

Unit Dimensions




Allow door swing clearance at locations next to a wall. The refrigerator door must open to a minimum of 90° to allow the crispers to open and the shelves to be removed.



Height can be increased by 1-1/2" (40 mm) by turning the levelling feet at the front and the height adjustable roller units at the appliance rear.


Cabinet Opening Dimensions



| Inset cabinet Depth D | Frameless cabinet Depth D |
|-----------------------|---------------------------|
| 24" + panel thickness | 24"                       |

Factory available stainless steel panels are designed for an inset installation only and require a cabinet / gable depth of 24 - 3/4".

Panel Dimensions



Inset Installation Style

Minimum panel thickness is 5/8" (16 mm).

Maximum panel thickness is 3/4" (19 mm).

Maximum weight of each panel is 26.5 lbs (12 kg).

| Cabinet opening A | Refrigerator door panel B |
|-------------------|---------------------------|
| 80"               | 45-1/4" (1150 mm)         |
| 84"               | 49-1/4" (1251 mm)         |

Frameless Installation Style


Minimum panel thickness is 5/8" (16 mm).

Maximum panel thickness is 3/4" (19 mm).

Maximum weight of each panel is 26.5 lbs (12 kg).

| Cabinet opening A | Refrigerator door panel B |
|-------------------|---------------------------|
| 80"               | 45-3/4" (1162 mm)         |
| 84"               | 49-3/4" (1264 mm)         |

Ventilation Requirements



The appliance do not require ventilation considerations in the cabinetry. The required airflow is directed through the toe kick base. It is important to use the provided cover grille for the ventilation opening. This opening must not be covered.

# PROF365CTXV

PROFESSIONAL SERIES

36" FRONT CONTROL GAS COOKTOP 5 BURNERS



Bring Italian design and precision into your kitchen with the Bertazzoni front-control gas cooktop, designed to install almost flush with the countertop.

Cook like a pro on the 5 flexible burners and cast iron contour grates, spaciouly laid out to accommodate pots of different sizes.

Crank up the heat to boil water, sear meat or cook with a wok using the power burner with dual ring flame, which boils water faster than any burner in its class (19,000 BTUs with LP gas).

Delicately melt chocolate on the simmer burner.

Protect your house and your family with the 100% fail-safe thermocouple technology that immediately shuts off the flow of gas in case of a flame outage.

Clean in no time after cooking, thanks to the seamless one-piece stainless worktop with no gaps, joints or fasteners.

This cooktop is ideal for installation over a Bertazzoni oven because of its extremely low-depth design.

ADA compliant.

Designed and manufactured with pride by Bertazzoni in Italy.

Industry leading 2 years parts and labor warranty.

| PRODUCT FEATURES                |                                                                                                               |
|---------------------------------|---------------------------------------------------------------------------------------------------------------|
| Maintop                         | 5 burners                                                                                                     |
| Burner power                    | 1 power burner 17000 BTU<br>1 rapid burner 10400 BTU<br>2 medium burners 6000 BTU<br>1 simmer burner 3750 BTU |
| Ignition system                 | Electric with thermocouple safety device                                                                      |
| Grates                          | Cast iron                                                                                                     |
| Included accessories            | Simmer ring                                                                                                   |
| TECHNICAL SPECIFICATIONS        |                                                                                                               |
| Electrical supply               | 120 V 60 HZ - 1 W<br>1 Amps                                                                                   |
| Power connection                | NEMA 5-15P with 59" power cord                                                                                |
| Certification                   | UL                                                                                                            |
| Warranty                        | 2 years parts & labor                                                                                         |
| Gas type                        | NG                                                                                                            |
| Conversion kit included         | LPG                                                                                                           |
| Packaging dimensions and weight | W 38"<br>H 8 3/8"<br>D 23 1/2"<br>46.5 lbs                                                                    |



# PROF365CTXV


PROFESSIONAL SERIES

36" FRONT CONTROL GAS COOKTOP 5 BURNERS




## PRODUCT DIMENSIONS

TOP VIEW




FRONT VIEW



SIDE VIEW



## ELECTRICAL & GAS CONNECTION



E

A properly-grounded, horizontally-mounted electrical receptacle should be installed according to this drawing.

G

An agency-approved, properly-sized manual shut-off valve should be installed according to this drawing.


## INSTALLATION REQUIREMENTS

Combustible material cannot be installed within shaded area.


For installation with an updraft or downdraft hood as well as any OTR, refer to the hood/OTR manufacturer's installation requirements.

## CUTOUT DIMENSIONS


TOP VIEW



SIDE VIEW



FRONT VIEW



For installation of multiple products in combination, refer to the Design Guide at [us.bertazzoni.com](http://us.bertazzoni.com) or [ca.bertazzoni.com](http://ca.bertazzoni.com)

**Disclaimer:** while every effort has been made to ensure the accuracy of the information contained in this document, Fratelli Bertazzoni reserves the right to change it at any time without notice. For detailed installation instructions, consult the installation manual. Fratelli Bertazzoni, Bertazzoni and the winged wheel brand icon are registered trademarks of Bertazzoni Spa.

## 30 Electric Convection Oven Self-Clean Professional Series



### PROF30FSEXV

Bertazzoni built-in ovens put Italian design and precision at the heart of your kitchen. As beautiful as they are practical, they can be installed flush or proud in any style of kitchen cabinet.

With technology designed to help you cook any dish to perfection, the Bertazzoni dual diagonal convection fans offer best-in-class even heat distribution throughout the extra-large 4.1 cu.ft oven cavity. Evenly bake large batches of cookies using all 7 shelf positions. The full-width 8-pass broiler sears steaks so they are crisp on the outside and juicy inside. Or use it to broil delicate fish fillets to perfection. And when you've finished cooking, the no-fingerprint stainless steel is easy to clean.

Bertazzoni built-in ovens are designed with pride in Italy and covered by an industry-leading 2-year parts and labor warranty.

# Specifications

## Features

### Oven cavity

|                        |                                                                                                                                                                                      |
|------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Size                   | 30 in                                                                                                                                                                                |
| Oven configuration     | single                                                                                                                                                                               |
| Oven fuel              | electric                                                                                                                                                                             |
| Oven broiler type      | electric                                                                                                                                                                             |
| Oven functions         | bake / broil / convection / convection bake / convection broil / defrosting / dehydra / fast preheat / oven light / pizza / proofing / pyrolytic self clean / sabbath mode / warming |
| Overall volume         | 4.10 ft³                                                                                                                                                                             |
| Oven convection system | dual diagonal with heating element                                                                                                                                                   |
| Oven controls          | knobs / touch LED display                                                                                                                                                            |
| Inner oven door        | quadruple                                                                                                                                                                            |
| Removable inner glass  | yes                                                                                                                                                                                  |
| Cavity finishing       | pyrolytic grey enamel                                                                                                                                                                |
| Oven handle            | metal                                                                                                                                                                                |
| Cooling fan            | yes                                                                                                                                                                                  |
| Oven levels            | 7                                                                                                                                                                                    |
| Timer                  | touch digital programmer                                                                                                                                                             |
| Door hinge             | soft-motion                                                                                                                                                                          |
| Wire-shelves           | 1 flat / 1 shaped                                                                                                                                                                    |
| Tray                   | 1 baking tray with roasting trivet                                                                                                                                                   |
| Grill trivet for tray  | yes                                                                                                                                                                                  |
| Oven lights            | single                                                                                                                                                                               |

### Technical specifications


|                   |                                                                                |
|-------------------|--------------------------------------------------------------------------------|
| Electrical supply | 120/240 V 60 Hz - 5500 W / 120/208 V 60 Hz - 4400 W / 30 Amp dedicated circuit |
| Power connection  | metal conduit 59" power cord                                                   |
| Certification     | CSA                                                                            |
| Power rating      | Bake: 5400W / Broiler: 3400 W / Convection: 3300 W                             |



---

## Dimensions

---



# CRISTAL SS SLIDE OUT RANGE HOOD



**POWERFUL, PRACTICAL, EFFICIENT SLIDE OUT RANGE HOOD.** For a streamlined look in the kitchen, the Cristal SS slide out hood is your integrated choice with a Stainless Steel pull-out visor which slides in, neatly tucking the hood away. For total integration, the front visor panel can be replaced with material to match your cabinets. NEW - WITH ENERGY EFFICIENT LED LIGHTS AND A CONVENIENT POWER PLUG

**NOW WITH LED  
BULBS AND POWER  
PLUG  
600, 400, 300 CFM  
versions**

**Now with a Black Stainless  
Trim Kit!**

## AVAILABLE MODELS

| Model #     | Size / Color | Motor Class (CFM) | Sound Levels (sones) |
|-------------|--------------|-------------------|----------------------|
| CRIS30SS600 | 30 SS        | 600               | 3.5 - 6.5            |
| CRIS36SS600 | 36 SS        | 600               | 3.5 - 6.5            |
| CRIS30SS400 | 30 SS        | 400               | 3.0 - 6.0            |
| CRIS36SS400 | 36 SS        | 400               | 3.0 - 6.0            |
| CRIS30SS300 | 30 SS        | 300               | 2.0 - 5.0            |
| CRIS36SS300 | 36 SS        | 300               | 2.0 - 5.0            |

## KEY FEATURES



### Auto on/off with pull out visor

Lights and fan turn on automatically when you slide the hood visor out.




### VariDuct System

Top and Rear Direct Venting  
Easy kitchen integration with top and direct rear venting and recirculation options.



### EasySnap Mounting Clips

Installation with easy built-in adjustable clips that tighten onto the sides of the cabinet floor.



### Fully Customizable Front Trim

Front visor trim can easily be integrated into your kitchen decor with accessory kit panels or fully customize for your own kitchen.

# CRISTAL SS

SLIDE OUT RANGE HOOD


**FABER**  
AIR MATTERS

## SPECIFICATIONS


|                                            |                                          |
|--------------------------------------------|------------------------------------------|
| cabinet cut out                            | 25 1/2" or 31 1/2" (W) x 10" (D)         |
| convertible to ductless / recirculating    | yes - with FILTER1 & FILTER1LL           |
| controls                                   | 3 speed slider                           |
| mounting height from cooking surface       | 24" - 30"                                |
| lighting                                   | 2 x 3 (w) LED <b>(NEW)</b>               |
| ducting top / direct rear vent (Vari-Duct) | 6" round                                 |
| grease filters                             | 4 dishwasher safe mesh filters           |
| auto on/off                                | yes - fan/lights turn on when pulled out |
| make up air compliant *                    | yes - 400 OR 300 cfm version option      |
| integrate front panel                      | yes - use your own custom front          |

## PERFORMANCE

| MODEL | SPEED 1 | 2   | 3   |
|-------|---------|-----|-----|
| SS600 | 335     | 450 | 560 |
| SS400 | 250     | 350 | 390 |
| SS300 | 100     | 200 | 290 |



Cabinet Cut Out 30" and 36"



Front View

## ACCESSORIES

### # FILTER1 - Charcoal Filter Kit

High quality charcoal filter for use when recirculating the air back into the kitchen. Filters out odor and should be replaced every 6 months or earlier depending on use

### # FILTER1LL - Long Lasting Charcoal Filter Kit

New washable charcoal filter can be recharged and washed up to 8 times. For use when recirculating the air back into the kitchen. Filters out odor and can last up to 4 years

### # MUDAMPER6 / MUDAMPER8 - Universal Make-Up Air Damper

Satisfies make-up air requirements, this kit uses an air switch to activate the make-up air damper to open and bring fresh air into the home when the hood fan is on. It then closes tightly when the hood is off. The CFM level is not reduced with this accessory.

### # CRTRIM30WH - (30" white)

### # CRTRIM30BK - (30" black)

### # CRTRIM36WH - (30" white)

### # CRTRIM36BK - (30" black)

### Front Trim Kit

Replace the stainless trim on the slide out hood with a black or white trim.

### # CRTRIM30BS - (30" black)


### Black Stainless Front Trim Kit

### # CRTRIM36BS - (36" black)


### Black Stainless Front Trim Kit

### # WIREBOX - Fixed Wiring Box

Replace the power cord with a hard wired box to power the range hood




Side View Top Vent



Side Direct Rear Vent

## Custom Front Trim Dimensions



30" or 36"

WARNING! Product specifications are subject to change without notification. Consult the installation instructions before you begin installing this range hood. \* Check local make up air codes for guidelines.



# 24" Custom Panel Dishwasher

300 Series – Custom Panel SHVM63W53N



**BOSCH**  
Invented for life



**SHVM63W53N**  
Custom Panel

**The 3rd rack provides the perfect space for silverware and large utensils while its V shape leaves room below for taller items.**

## Features & Benefits

44 dBA: dishwasher runs quietly so your kitchen conversations aren't interrupted.

With PrecisionWash®, intelligent sensors and precision spray arms target every item of every load, so dishes come out sparkling clean every time.

The AquaStop® leak protection system contains leaks through a precisely engineered system. If a leak occurs, the system contains it by shutting down operation and pumping out water. So you have the ultimate peace of mind whether you are away or at home.

## General Properties

|                                 |                              |
|---------------------------------|------------------------------|
| Number of wash cycles           | 5                            |
| Number of options               | 4                            |
| dBA                             | 44                           |
| Drying system                   | PureDry                      |
| Third rack                      | Standard 3rd Rack            |
| Rack adjustability              | Rackmatic®                   |
| Tub material                    | Stainless Steel              |
| Control type                    | Buttons                      |
| Concealed water heating element | Yes                          |
| Leak protection system          | 24/7 AquaStop®               |
| NSF®-certified* sanitize option | Yes                          |
| Water softener                  | No                           |
| Five-level wash                 | Yes                          |
| ChildLock                       | No                           |
| Special features                | InfoLight®, Extra Dry Option |

## Efficiency

|                                       |        |
|---------------------------------------|--------|
| Water usage per cycle                 | 3.5    |
| Energy efficiency class               | Tier 1 |
| ENERGY STAR® qualified                | Yes    |
| Total annual energy consumption (kWh) | 269    |
| Total annual water consumption (g)    | 623.5  |

## Capacity

|                          |    |
|--------------------------|----|
| Number of place settings | 16 |
|--------------------------|----|

## Technical Details

|                                                                         |                           |
|-------------------------------------------------------------------------|---------------------------|
| Watts (W)                                                               | 1440 W                    |
| Current (A)                                                             | 12 Amps                   |
| Volts (V)                                                               | 120 V                     |
| Frequency (Hz)                                                          | 60 Hz                     |
| Power cord full length                                                  | 67"                       |
| Power cord install length from edge of unit when facing the door (in)** | Left – 45"<br>Right – 56" |
| Minimum water pressure (lb/sin)                                         | 14                        |
| Length outlet hose (in)                                                 | 79"                       |

## Dimensions & Weight

|                                           |                               |
|-------------------------------------------|-------------------------------|
| Overall appliance dimensions (HxWxD) (in) | 33 7/8" x 23 9/16" x 23 1/16" |
| Required cutout size (HxWxD) (in)         | 33 7/8" x 23 5/8" x 24"       |
| Adjustable feet                           | Yes                           |
| Net weight (lbs)                          | 88 lbs                        |

## Accessories—Optional

|                                              |            |
|----------------------------------------------|------------|
| Junction Box                                 | SMZPCJB1UC |
| Bosch Dishwasher Water Supply Hose           | SMZSH002UC |
| Drain Hose Extension Kit                     | SGZ1010UC  |
| Stainless Steel Straight Bosch Bar Handle    | SMZ1007UC  |
| Dishwasher Accessory Kit                     | SMZ5000    |
| Anti-Tarnish Silverware Cassette             | SMZ5002UC  |
| Edge Protector + Power Cord Clip Install Kit | SMZEPCC1UC |



\*Certification to NSF/ANSI Standard 184 for residential dishwashers

\*\*September 2020 running production change to remove adhesive routing clips for power cord. These clips and the edge protector are now included in the dishwasher accessory kit # SMZEPCC1UC.

**Accessories:** To purchase Bosch accessories, cleaners & parts please visit [www.bosch-home.com/us/store](http://www.bosch-home.com/us/store) or call 1-800-944-2904 (Mon to Fri 5 am to 6 pm PST, Sat 6 am to 3 pm PST).

**Notes:** All height, width and depth dimensions are shown in inches. BSH reserves the absolute and unrestricted right to change product materials and specifications, at any time, without notice. Consult the product's installation instructions for final dimensional data and other details prior to making cutout.

**Warranties:** Please see Use & Care manual or Bosch website for statement of limited warranty.

**For more information on our entire line of products, go to [www.bosch-home.com/us](http://www.bosch-home.com/us) or call 1-800-944-2904**

© BSH Home Appliances Corporation. All rights reserved. Bosch is a registered trademark of Robert Bosch GmbH.






# 24" Custom Panel Dishwasher

300 Series – Custom Panel SHVM63W53N



**BOSCH**  
Invented for life

## Installation Details



**Accessories:** To purchase Bosch accessories, cleaners & parts please visit [www.bosch-home.com/us/store](http://www.bosch-home.com/us/store) or call 1-800-944-2904 (Mon to Fri 5 am to 6 pm PST, Sat 6 am to 3 pm PST).

**Notes:** All height, width and depth dimensions are shown in inches. BSH reserves the absolute and unrestricted right to change product materials and specifications, at any time, without notice. Consult the product's installation instructions for final dimensional data and other details prior to making cutout.

**Warranties:** Please see Use & Care manual or Bosch website for statement of limited warranty.

**For more information on our entire line of products, go to [www.bosch-home.com/us](http://www.bosch-home.com/us) or call 1-800-944-2904**

© BSH Home Appliances Corporation. All rights reserved. Bosch is a registered trademark of Robert Bosch GmbH.





# 24" Custom Panel Dishwasher

300 Series – Custom Panel SHVM63W53N



**BOSCH**  
Invented for life

## Installation Details



Note: Plumbing installations will vary - refer to local codes. Drain hose included is 79" (201 cm) and can be extended to a maximum of 155 3/4" (396 cm).

Always use the approved drain hose extension kit (SGZ1010UC).

Ensure a portion of the drain hose is raised between min. 33" (84 cm) and max. 43" (110 cm) above the cabinet floor.

**Accessories:** To purchase Bosch accessories, cleaners & parts please visit [www.bosch-home.com/us/store](http://www.bosch-home.com/us/store) or call 1-800-944-2904 (Mon to Fri 5 am to 6 pm PST, Sat 6 am to 3 pm PST).

**Notes:** All height, width and depth dimensions are shown in inches. BSH reserves the absolute and unrestricted right to change product materials and specifications, at any time, without notice. Consult the product's installation instructions for final dimensional data and other details prior to making cutout.

**Warranties:** Please see Use & Care manual or Bosch website for statement of limited warranty.

**For more information on our entire line of products, go to [www.bosch-home.com/us](http://www.bosch-home.com/us) or call 1-800-944-2904**

© BSH Home Appliances Corporation. All rights reserved. Bosch is a registered trademark of Robert Bosch GmbH.

LG LAUNDRY

WM3488H\_

2.3 cu.ft. Compact All-In-One Washer/Dryer

- 2.3 cu.ft. Capacity
- Compact All-In-One Washer/Dryer Combo
- 14 Wash Programs
- 1,400 RPM
- Ventless Condensing Drying
- Internal Heater
- NFC Tag On
- Available in White and Silver



| CAPACITY                            |                                                                                                                                                                                  |
|-------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Capacity                            | 2.3 cu. ft.                                                                                                                                                                      |
| APPEARANCE                          |                                                                                                                                                                                  |
| Design Look                         | Front Control                                                                                                                                                                    |
| Touch LED Display                   | •                                                                                                                                                                                |
| Dial-A-Cycle™                       | •                                                                                                                                                                                |
| WASH/DRY PROGRAMS                   |                                                                                                                                                                                  |
| No. of Programs                     | 14                                                                                                                                                                               |
| Wash Programs                       | Cotton/Normal, Bulky/Large, Baby Wear, Perm. Press, Delicates, Hand Wash/Wool, Speed Wash, Tub Clean, Sanitary, Heavy Duty, Drain+Spin, Wash+Dry, Sports Wear, Downloaded Course |
| No. of Options                      | 10                                                                                                                                                                               |
| Options                             | Prewash, Rinse+Spin, Delay Wash(Time Delay), Water Plus, Extra Rinse, Child Lock, Signal (Beeper) On/Off, Steam, Custom PGM, PGM Save                                            |
| No. of Wash/Rinse Temps             | 5                                                                                                                                                                                |
|                                     | Extra Hot, Hot, Warm, Cold, Tap Cold (All Cold Rinses)                                                                                                                           |
| Spin Speeds                         | Extra High (1,400 max.), High, Medium, Low, No Spin                                                                                                                              |
| No. of Water Levels                 | Automatically adjusts to the size of load                                                                                                                                        |
| No. of Soil Levels                  | 3                                                                                                                                                                                |
| Internal Heater                     | •                                                                                                                                                                                |
| Ventless Condensing Dryer           | •                                                                                                                                                                                |
| Drying Levels                       | More Dry, Normal Dry, Damp Dry, Low Temp Dry                                                                                                                                     |
| Manual Dry Times                    | 120, 60., 30 minutes                                                                                                                                                             |
| CONVENIENCE FEATURES                |                                                                                                                                                                                  |
| TrueBalance™ Anti-Vibration System" | •                                                                                                                                                                                |
| 4 Tray Dispenser                    | •                                                                                                                                                                                |
| LoDecibel™ Quiet Operation          | •                                                                                                                                                                                |
| End of Cycle Beeper                 | •                                                                                                                                                                                |
| LoadSense                           | •                                                                                                                                                                                |
| Forced Drain System                 | •                                                                                                                                                                                |
| SMART THING™ TECHNOLOGY             |                                                                                                                                                                                  |
| SmartDiagnosis™                     | •                                                                                                                                                                                |
| NFC Tag On Technology               | •                                                                                                                                                                                |

| MOTOR AND AGITATOR                                       |                                                   |
|----------------------------------------------------------|---------------------------------------------------|
| Motor Type                                               | Inverter Direct Drive Motor                       |
| Motor Speed                                              | Variable                                          |
| Max RPM                                                  | 1,400                                             |
| Axis                                                     | Horizontal                                        |
| MATERIALS AND FINISHES                                   |                                                   |
| NeveRust™ Stainless Steel Drum                           | •                                                 |
| Cabinet                                                  | PCM                                               |
| Control Panel                                            | Plastic                                           |
| Top Plate                                                | TBD                                               |
| Door Rim                                                 | Glass/Chrome                                      |
| Door Cover                                               | Black Tinted Cover                                |
| Door Opening                                             | 13.8"                                             |
| Available Colors                                         | White (W), Silver (S)                             |
| POWER SOURCE                                             |                                                   |
| Ratings                                                  | TBD                                               |
| Electrical Requirements                                  | 120V, 10 Amps                                     |
| Type                                                     | Electric                                          |
| ACCESSORIES                                              |                                                   |
| Hose Included                                            | •                                                 |
| DIMENSIONS                                               |                                                   |
| Product (WxHxD)                                          | 24" x 33 1/2" x 25 1/4"<br>(45" D with door open) |
| Carton (WxHxD)                                           | 26" x 35 3/4" x 27 3/4"                           |
| Weight (Product/Carton)                                  | 156.5 lbs / 165.3 lbs                             |
| LIMITED WARRANTY                                         |                                                   |
| 1 Year Parts and Labor, 10 Years Motor, Lifetime on Drum |                                                   |
| UPC CODES                                                |                                                   |
| WM3488HW Washer/Dryer (White)                            | 048231 016988                                     |
| WM3488HS Washer/Dryer (Silver)                           | 048231 016995                                     |